

# Personal Protective Equipment

## Purpose

The Town of Weston provides all employees with required Personal Protective Equipment (PPE) to suit the task and known hazards. This chapter covers the requirements for PPE with the exception of PPE used for hearing conservation and respiratory protection or PPE required for hazardous material response to spills or releases, which are covered under separate programs.

## General Policy

Engineering controls shall be the primary methods used to eliminate or minimize hazard exposure in the workplace. When such controls are not practical or applicable, personnel protective equipment shall be employed to reduce or eliminate personnel exposure to hazards. Personal Protective Equipment will be provided, used, and maintained when it has been determined that its use is required and that such use will lessen the likelihood of occupational injuries and/or illnesses.

## Responsibilities

### Management: The Road Foreman will be Responsible for

- Conduct hazard assessments to identify specific PPE for specific tasks.
- Train employees in the selection, use, inspection, storage, cleaning, and limitations of specific PPE.
- Monitor use of PPE.
- Provide replacement PPE when needed.
- Identify any new hazards that would require the use of PPE.

### Employees Will:

- Properly use and care for assigned PPE.
- Immediately inform management if PPE is damaged or not effective

## General Rules

### Design

All personal protective clothing and equipment will be of safe design and construction for the work performed. Only those items of protective clothing and equipment that meet the National Institute of Occupational Safety and Health (NIOSH) or American National Institute (ANSI) Standards will be procured or accepted for use.

### Hazard Assessment and Equipment Selection.

Hazard analysis procedures shall be used to assess the workplace to determine if hazards are present, or are likely to be present, the following actions will be taken:

- Select, and have each affected employee use, the proper PPE.
- Communicate selection decisions to each affected employee.
- Select PPE that properly fits each affected employee.

**Defective and damaged equipment.**

Defective or damaged personal PPE shall not be used.

**Training**

All employees who are required to use PPE shall be trained to know at least the following:

- When PPE is necessary;
- What PPE is necessary;
- How to properly put on, remove, adjust, and wear PPE;
- The limitations of PPE
- The proper care, maintenance, useful life, and dispose of the PPE.

Each affected employee shall demonstrate an understanding of the training and the ability to use PPE properly, before being allowed to perform work requiring the use of PPE.

Certification of training for the PPE is required by OSHA and shall be accomplished by using the job safety checklist to verify that each affected employee has received and understood the required PPE training.

**PPE Selection****Controlling Hazards,**

PPE devices alone should not be relied on to provide protection against hazards, but should be used in conjunction with guards, engineering controls, and sound manufacturing practices.

**Selection guidelines.**

The general procedure for selection of protective equipment is to:

- a) become familiar with the potential hazards and the type of protective equipment that is available, and what it can do: i.e., splash protection, impact protection, etc.
- b) compare the hazards associated with the environment; impact velocities, masses, projectile shape, radiation intensities, with the capabilities of the available protective equipment;
- c) select the protective equipment that ensures a level of protection greater than the minimum required to protect employees from the hazards.
- d) fit the user with the protective device and give instructions on care and use of the PPE. It is very important that the end users be made aware of all warning labels for and limitations of their PPE.

**Fitting the device**

Careful consideration must be given to comfort and fit. PPE that fits poorly will not afford the necessary protection Continued wearing of the device is more likely if it fits the wearer comfortably. Protective devices are generally available in a variety of sizes. Care should be taken to ensure that the right size is selected.

**Devices with adjustable features.**

Adjustments should be made on an individual basis for a comfortable fit that will maintain the protective device in the proper position. Particular care should be taken in fitting the devices for eye protection against dust and chemical splash to ensure that the devices are sealed to the face. In addition, proper fitting of helmets is important to ensure that it will not fall off during work operations. In some cases, a chinstrap may be necessary to keep the helmet on an employee's head. (Chinstraps should break at a reasonably low force, however, to prevent a strangulation hazard). Where manufacturer's instructions are available, they should be followed carefully.

**Eye and Face Protection,**

The majority of occupational eye injuries can be prevented by the use of suitable approved safety spectacles, goggles, or shields. Approved eye and face protection shall be worn when there is a reasonable possibility of personal injury.

- Each employee shall use appropriate eye or face protection when exposed to eye or face hazards from flying particles, molten metal, liquid chemicals, acids or caustic liquids, chemical gases or vapors, or potentially injurious light radiation.
- Each employee shall use eye protection that provides side protection when there is a hazard from flying objects. Detachable side protectors are acceptable.
- Each employee who wears prescription lenses while engaged in operations that involve eye hazards shall wear eye protection that incorporates the prescription in its design, or shall wear eye protection that can be worn over the prescription lenses without disturbing the proper position of the prescription lenses or the protective lenses.
- Eye and face PPE shall be distinctly marked to facilitate identification of the manufacturer.
- Each employee shall use equipment with filter lenses that have a shade number appropriate for the work being performed for protection from injurious light radiation.

**Typical hazards that can cause eye and face injury are:**

- Splashes of toxic or corrosive chemicals, hot liquids, and molten metals;
- Flying objects, such as chips of wood, metal, and stone dust;
- Fumes, gases, and mists of toxic or corrosive chemicals; and
- Aerosols of biological substances.

Prevention of eye accidents requires that all persons who may be in eye hazard areas wear protective eyewear. This includes employees, visitors, contractors, or others passing through an identified eye hazard area. To provide protection for these personnel, activities shall procure a sufficient quantity of heavy-duty goggles and/or plastic eye protectors, which afford the maximum amount of protection possible. If these personnel wear personal glasses, they shall be provided with a suitable eye protector to wear over them.

**Eye/Face Protection Specifications**

Eye and Face protectors procured, issued to, and used by employees, contractors, and visitors must conform to the following design and performance standards:

- a) Provide adequate protection against the particular hazards for which they are designed.
- b) Fit properly and offer the least possible resistance to movement and cause minimal discomfort while in use.
- c) Be durable
- d) Be easily cleaned or disinfected for or by the wearer.
- e) Be clearly marked to identify the manufacturer.
- f) Person who require corrective lenses for normal vision, and who are required to wear eye protection, must wear goggles or spectacles of one of the following types;
  - 1) Spectacles with protective lenses, which provide optical correction.
  - 2) Goggles that can be worn over spectacles without disturbing the adjustment of the spectacles.
  - 3) Goggles that incorporate corrective lenses mounted behind the protective lenses.

## **Eye & Face Protector Use**

### **Safety Spectacles.**

Protective eyeglasses are made with safety frames, tempered glass, or plastic lenses, temples and side shields, which provide eye protection from moderate impact and particles encountered in job tasks such as carpentry, woodworking, grinding, scaling, etc.

### **Single Lens Goggles,**

Vinyl framed goggles of soft pliable body design provide adequate eye protection from many hazards. These goggles are available with clear or tinted lenses, perforated, port vented, or non-vented frames. Single lens goggles provide similar protection to spectacles and may be worn in combination with spectacles or corrective lenses to insure protection along with proper vision.

### **Welders/Chippers Goggles.**

These goggles are available in rigid and soft frames to accommodate single or two eyepiece lenses.

- 1) Welders goggles provide protection from sparking, scaling, or splashing metals and harmful light rays. Lenses are impact resistant and are available in graduated shades of filtration.
- 2) Chippers/grinders goggles provide eye protection from flying particles. The dual protective eyecups house impact resistant clear lenses with individual cover plates.

### **Face Shields.**

These normally consist of an adjustable headgear and face shield of tinted/transparent acetate or polycarbonate materials, or wire screen. Face shields are available in various sizes, tensile strength, impact/heat resistance, and light ray filtering capacity. Face shields will be used in operations when the entire face needs protection and should be worn to protect eyes and face against flying particles, metal sparks, and chemical/biological splash.

**Welding Shields**

These shield assemblies consist of volcanized fiber or glass fiber body, a ratchet/button type headgear or cap attachment and a filter and cover plate holder. These shields will be provided to protect workers'

**Filter Lenses for Protection against Radiant Energy**

Operations	Electrode Size 1/32 in	Arc Current	Protective Shade
Shielded Metal Arc	Less than 3	Less than 60	7
Welding			
	3 – 5	60 – 160	8
	5 – 8	160 – 250	10
	More than 8	250 – 550	11
Torch Brazing			3
Torch Soldering			2

**Note:** as a rule of thumb, start with a shade that is too dark to see weld zone. Then go to a lighter shade, which gives sufficient view of the weld zone without going below the minimum. In oxyfuel gas welding or cutting where the torch produces a high yellow light, it is desirable to use a filter lens that absorbs the yellow or sodium line in the visible light of the (spectrum) operation.

**Selection Chart Guidelines for Eye and Face Protection**

The following chart provides general guidance for the proper selection of eye and face protection to protect against hazards associated with the listed hazard "source" operations.

Source	Hazard	Protection
<b>IMPACT</b> – Chipping, grinding machining, masonry work, woodworking, sawing, drilling, chiseling, powered fastening, riveting, and sanding.	Flying fragments, objects, large chips, particles, sand, dirt, etc.	Spectacles with side protection, goggles, face shield. For severe exposure, use face shield.
<b>HEAT</b> – Furnace operation and arc welding	Hot Sparks	Face Shields, spectacles with side protection For severe exposure use face shield.

<b>CHEMICALS</b> – Acid and chemical handling, degreasing, plating.	Splash	Goggles, eyecup and cover types, For severe exposure, use face shield
<b>Dust</b> – Woodworking, buffing general buffing, general dusty conditions.	Nuisance dust	Goggles, eye cup and cover type.

### Head Protection

Hats and caps have been designed and manufactured to provide workers protection from impact, heat, electrical and fire hazards. These protectors consist of the shell and the suspension combined as a protective system. Safety hats and caps will be of nonconductive, fire and water resistant materials. Bump caps or skull guards are constructed of lightweight materials and are designed to provide minimal protection against hazards when working in congested areas.

Head protection will be furnished to, and used by, all employees and contractors engaged in construction and other miscellaneous work in head-hazard areas. Head protection will also be required to be worn by engineers, inspectors, and visitors at construction sites. Bump caps/skull guards will be issued to and worn for protection against scalp lacerations from contact with sharp objects. They will not be worn as substitutes for safety caps/hats because they do not afford protection of falling objects.

#### Selection guidelines for head protection.

All head protection is designed to provide protection from impact and penetration hazards caused by falling objects. They will not be worn as substitutes for safety caps/hats because they do not afford protection from high impact forces or penetration of falling objects.

### Foot Protection

#### General Requirements

Each affected employee shall wear protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects, or piercing the sole, and where employee's feet are exposed to electrical hazards.

#### Selection guidelines for foot protection.

Safety shoes and boots provide both impact and compression protection. Where necessary, safety shoes can be obtained which provide puncture protection. In some situations, metatarsal protection should be provided, and in other special situations, electrical conductive or insulating safety shoes would be appropriate. Safety shoes or boots with impact protection would be required for carrying or handling materials such as packages, objects, parts, or heavy tools, which could be dropped; and, for all other activities where objects might fall onto the feet. Safety shoes or boots with compression protection would be required for work involving skid tracks (manual material handling carts) around bulk rolls (such as paper rolls) and around heavy pipes, all of which could potentially roll over an employee's feet. Safety shoes or boots with puncture protection would be required where sharp objects such as nails, wire, tacks, screws, large staples, scrap metal etc., could be stepped on by employees causing a foot injury.

## **Hand Protection**

### **General Requirements**

Hand protection is required when employees' hands are exposed to hazards such as those from skin absorption of harmful substances; severe cuts or lacerations; severe abrasions; punctures; chemical burns; thermal burns; and harmful temperature extremes.

Skin contact is a potential source of exposure to toxic materials; it is important that the proper steps be taken to prevent such contact. Gloves should be selected based on the material being handled, the particular hazard involved, and their suitability for the operation being conducted. One type of glove will not work in all situations.

Most accidents involving hands and arms can be classified under four main hazard categories: Chemicals, abrasions, cutting, and heat. There are gloves available that can protect workers from any of these individual hazards or combination of hazards.

Gloves should be replaced periodically, depending on frequency of use and permeability to the substance(s) handled. Gloves overtly contaminated should be rinsed and then carefully removed after use.

Gloves should also be worn whenever it is necessary to handle rough or sharp edged objects, and very hot or very cold materials. The types of glove materials to be used in these situations include leather, welder's gloves, aluminum-backed gloves, and other types of insulated glove materials.

Careful attention must be given to protecting your hands when working with tools and machinery. Power tools and machinery must have guards installed or incorporated into their design that prevent the hands from contacting the point of operation, power train, or other moving parts, it is important to:

- Ensure that the guards are always in places and used,
- Always lock out machines or tools and disconnect the power before making repairs,
- Treat a machine without a guard as inoperative; and
- Do not wear gloves around moving machinery, such as drill presses, mills, lathes, and grinders.

### **Selection guidelines for hand protection**

Selection of hand PPE shall be based on an evaluation of the performance characteristics of the hand protection relative to the task(s) to be performed, conditions present, duration of use, and the hazards and potential hazards identified. Gloves are often relied upon to prevent cuts, abrasions, burns, and skin contact with chemicals that are capable of causing local or systemic effects following dermal exposure. There is no glove that provides protection against all potential hand hazards, and commonly available glove materials provide only limited protection against many chemicals. Therefore, it is important to select the most appropriate glove for a particular application and to determine how long it can be worn, and whether it can be reused. It is also important to know the performance characteristics of gloves relative to the specific hazard anticipated; e.g. chemical hazard, cut hazards, flame hazards, etc. Before purchasing gloves, request documentation from the manufacturer that the gloves meet the appropriate test standard(s) for the hazard(s) anticipated. Other factors to be considered for glove selection include:

(A) As long as the performance characteristics are acceptable, in certain circumstances, it may be more cost effective to regularly change cheaper gloves than to reuse types that are more expensive.

(B) The work activities of the employee should be studied to determine the degree of dexterity required, the duration, frequency, and degree of exposure of the hazard, and the physical stresses that will be applied.

**Selection of gloves for chemical hazards.**

The first consideration in the selection of gloves for use against chemicals is to determine, if possible, the exact nature of the substances to be encountered. Read instructions and warnings on chemical container labels and MSDSs before working with any chemical. Recommended glove types are often listed in the section for personal protective equipment.

All glove materials are eventually permeated by chemicals. However, they can be used safely for limited time periods if specific use and glove characteristics (i.e. thickness and permeation rate and time) are known. The safety office can assist in determining the specific type of glove material that should be worn for a particular chemical.

(A) The toxic properties of the chemical(s) must be determined; in particular, the ability of the chemical to cause local effects on the skin and/or to pass through the skin and cause systemic effects.

(B) Generally, any "Chemical resistant" glove can be used for dry powders:

(C) For mixtures and formulated products (unless specific test data is available), a glove should be selected based on the chemical component with the shortest breakthrough time, since it is possible for solvents to carry active ingredients through polymeric materials.


(D) Employees must be able to remove the gloves in such a manner as to prevent skin contamination.

Adopted by the Weston Selectboard:

Date 12/13/2016

Revision Date \_\_\_\_\_

  
\_\_\_\_\_  
Denis Benson – Chairman

  
\_\_\_\_\_  
Ann Fuji'i – Secretary

  
\_\_\_\_\_  
Jim Linville – Vice Chairman

  
\_\_\_\_\_  
Charles Goodwin

  
\_\_\_\_\_  
Bruce Downer